



SYSTEM 5000

ADHESIVE PRESSURE SYSTEM



SINGLE COMPONENT SYSTEM

A simple way to deliver water based adhesives without pumps, pouring into pressure tanks or container elevation.


The System 5000 is a 55 gallon drum pressurization system. It is compatible only with 3M approved 55 gallon drums, containing water based adhesives. The regulated pressure valve mounted on the 3/4" drum bung hole pressurizes the drum to a maximum of 7 PSI. The drum pressurization valve assembly includes an adhesive pressure regulator and atomization regulator. The quick disconnect feature makes changing drums easy.



PLURAL COMPONENT SYSTEM

The plural component system includes a regulated activator pump mounted on the rear of the pressurization valve assembly. Mounted on the 2" drum bung hole is the adhesive outlet valve. It is setup with a quick connecting cam-locked hose and plug for easy attachment and mess-free removal when changing drums.

System 5000 includes a 95T gun for the single part adhesive version or the 95PCXT for the plural component version. Both are outfitted with the USL exclusive Tornado Nozzle. The vacuum created by the nozzle enhances fluid flow and helps reduce overspray.




Single part adhesives (#17-PD55)

- (1) 95T spray gun
- (1) Dual regulated pressurization valve assembly
- (1) Adhesive outlet assembly
- (1) 25' jacketed hose assembly

Plural component (#17-PD55-PC)

- (1) 95PCXT spray gun
- (1) Dual regulated pressurization valve assembly with mounted regulated activator pump
- (1) Adhesive outlet valve assembly
- (1) 25' jacketed hose assembly



- Additional 95T spray gun and 25' hose jacketed hose assembly
- Additional 95PCXT spray gun and 25' hose jacketed hose assembly

FOR ADDITIONAL INFORMATION:

Phone **530.477.4312** (7:30am-4pm PST)

Fax **530.477.4316**

Email **sprayit@uslegends.com**

Internet **www.uslegends.com**

Mail **United States Legends, Inc.**

972 Golden Gate Terrace

Grass Valley CA 95945

USA